

C20 TORK-SB20



VLASTNOSTI

TYP: Řada C20 , 6VA 5W Napětí: AC / DC



- C20.220.00.050 (TORK-SB20) : 220V AC
- C20.110.00.050 (TORK-SB21) : 110 V AC
- C20.024.00.050 (TORK-SB22) : 24V AC
- C20.012.00.050 (TORK-SB23) : 12V AV
- C20.024.01.050 (TORK-SB24) : 24V DC
- C20.012.01.050 (TORK-SB25) : 12 V DC
- Izolace měděného drátu(GR1) : H Class 180°C
- Krytí : IP 65 Socket DIN 40050
- Připojení : DIN43650 PG9

C50 TORK-SB50



NÁZEV	NAPĚTÍ	VÝKON	KRYTÍ
C50230VAC35VA	230 VAC	35VA	IP65
C50110VAC35VA	110 VAC	35VA	IP65
C50048VAC35VA	48 VAC	35VA	IP65
C50024VAC35VA	24 VAC	35VA	IP65
C50012VAC35VA	12 VAC	35VA	IP65
C50110VDC25W	110 VDC	25W	IP65
C50048VDC25W	48 VDC	25W	IP65
C50024VDC25W	24 VDC	25W	IP65
C50012VDC25W	12 VDC	25W	IP65